

KENWORTH

**TOP MOUNT ART 75-22**  
**2024 T880**

**NEW**

**AVAILABLE**



**SPECIFICATION**

**AVAILABLE: 10**

**OFFER INFORMATION**

Location details

572 Whitehead Rd # 301, Trenton, NJ, 08619 -

United States 

Dealer Name

PALFINGER American Roll-Off

Availability

**Available**

Product type

New

Contact person

James Hanson

Dealer E-mail

ja.hanson@palfinger.com

Dealer phone

**(267) 987-3444**

## TOP MOUNT ART 75-22

- 75,000 lb. capacity
- Operating pressure - 4,500 psi
- Outside rail capability
- Max dump angle 51°
- 18'- 22' container length range
- Containers less than 18' in length require short container stops

## HYDRAULICS

- Dual inboard single-stage lift cylinders
  - Eliminates interferences with outboard chassis components and allows for multiple lift axle installations
- (1) single-stage reeving cylinder
- 24.5 gpm direct mount piston pump, 4,500 psi main relief
- 35 gal. reservoir, w/100-micron suction strainer, and 25-micron canister style return line filter & 2" suction line shut-off valve
- 2-section directional valve

## CABLE

- 7/8" EIPS 6 x 37 domestic cable, fixed length with swivel hook

## SAFETY

- See-through reeving cylinder track guards
- (2) body props
- Patented automatic folding ICC bumper

## CHASSIS DETAILS

2024 Kenworth T880

- Fr Axle: 20,000 lbs
- Rr Axle: 46,000 lbs
- G.C.W: 85,000 lbs

### Engine & Transmission:

- Cummins X15, 500HP
- Allison 4500RDS

### Suspension:

- Front Axle: Taperleaf 20k
- Rear Axle: Tandem Chalmers 46k
- Watson Steerable Pusher Axle

### Fuel & Def:

- 100 Gallon aluminum
- 7.3 Gallon Def